NSN 5305-01-354-4232

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-354-4232 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.172 inches and 0.204 inches **Fastener Length:** Between 0.297 inches and 0.313 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.265 inches and 0.297 inches **Head Height:** Between 0.109 inches and 0.141 inches **Shoulder Diameter:** 0.155 inches first shoulder and 0.156 inches first shoulder **Shoulder Length:** 0.125 inches first shoulder and 0.127 inches first shoulder **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project Material: Plastic polyamide locking featuresteel comp 303 bearing surface of head **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-354-4232 Shoulder Screw - Page 2 of 2



Fiig:

A003b0