NSN 5305-01-354-4234

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-354-4234

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.480 inches and 0.500 inches |
| Fastener Length: |
| Between 3.230 inches and 3.250 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.543 inches and 0.563 inches |
| Head Height: |
| Between 0.240 inches and 0.250 inches |
| Shoulder Diameter: |
| 0.375 inches first shoulder |
| Shoulder Length: |
| 2.750 inches first shoulder |
| Shank Unthreaded Hole Diameter: |
| 0.078 inches first hole |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.312 inches |
| Width Across Flats: |
| 0.188 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Hardness Rating: |
| 32.0 rockwell c and 43.0 rockwell c |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 2.960 inches first hole and 2.980 inches first hole |
| Shoulder Shape: |
| Round first shoulder |
| Material: |
| Steel comp 4340 |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-354-4234

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0