## NSN 5305-01-354-4336

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-354-4336 **Thread Direction:** Right-hand Thread Length: Between 9.1 millimeters and 10.0 millimeters Fastener Length: 10.0 millimeters **Head Style:** Pan no. 2 **Head Diameter:** Between 4.1 millimeters and 5.0 millimeters **Head Height:** Between 1.3 millimeters and 1.5 millimeters **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 2.5 millimeters Min. Tensile Strength (psi): 1100 megapascals **Thread Pitch In Millimeters:** 0.45 **External Thread Tolerance Class:** 4h6h **Screw Material:** Iron alloy 660 **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 0.8 micrometers **Thread Surface Finish:** 0.8 micrometers **Thread Series Designator:** Μj **Specification Data:** 80205-nas0068 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:
-Demilitarization:

## NSN 5305-01-354-4336

Machine Screw - Page 2 of 2



Fiig:

A500d0