## NSN 5305-01-354-4684

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-354-4684 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.505 inches **Fastener Length:** Between 0.615 inches and 0.645 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.297 inches and 0.305 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.190 inches **Grip Length:** 0.125 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees Material: Steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416t+2cl2 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A003b0

## NSN 5305-01-354-4684

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.