NSN 5305-01-354-7236



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-354-7236 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** Between 1.016 inches and 1.046 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.3275 inches and 0.3325 inches **Shoulder Diameter:** 0.2177 inches first shoulder and 0.2182 inches first shoulder **Shoulder Length:** 0.615 inches first shoulder and 0.635 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure: Demilitarization: No

NSN 5305-01-354-7236

Shoulder Screw - Page 2 of 2



Fiig:

A003b0