## NSN 5305-01-354-8864



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-354-8864 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.620 inches **Fastener Length:** Between 0.734 inches and 0.781 inches **Head Style:** Hexagon **Head Height:** Between 0.049 inches and 0.060 inches Width Between Flats: Between 0.181 inches and 0.189 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-354-8864

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0