NSN 5305-01-355-1142

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-355-1142 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.517 inches **Fastener Length:** 0.560 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4140 or steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mils5626 military specification single material response or mils5000 military specification single material response or mils6049 military specification single material response **Head Surface Treatment:** Paint **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq+414ty2cl3 federal specification single treatment response **Special Features:** Furnished with boot type nylon washer 0.438 in. O.D. Head and washer color gray no. 26307, cagec 12324 **Thread Series Designator:**

Unc

Shelf Life:

Unit Of Measure:

N/a

NSN 5305-01-355-1142

Machine Screw - Page 2 of 2



em			

No

Fiig:

A500d0

Mil-std (military Standard):

spec.