NSN 5305-01-355-1419

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-355-1419 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.182 inches and 0.192 inches **Fastener Length:** 0.812 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.625 inches **Head Height:** Between 0.171 inches and 0.203 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches **Third Diameter From Head:** 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.490 inches and 0.510 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.812 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Qqs764, cond.A federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-355-1419

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0