

View Online at <https://aerobasegroup.com/nsn/5305-01-355-1987>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.463 inches

Fastener Length:

0.500 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Screw Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Screw Material Specification:

Mils5626 military specification single material response or mils5000 military specification single material response or mils6049 military specification single material response

Head Surface Treatment:

Paint

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq+416ty2cl3 federal specification single treatment response

Special Features:

Furnished with boot type nylon washer 0.312 in. O.D. Heas and washer color gray no.26307, cagec 12324

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

spec.