NSN 5305-01-355-3664

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-355-3664 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.300 inches and 0.310 inches **Fastener Length:** Between 0.990 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **First Diameter From Head:** Between 0.119 inches and 0.134 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.690 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Ms16995-30b military specification all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl4 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-355-3664

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.