

View Online at <https://aerobasegroup.com/nsn/5305-01-356-1573>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.208 inches and 0.228 inches

Fastener Length:

Between 0.510 inches and 0.550 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.265 inches and 0.297 inches

Head Height:

Between 0.109 inches and 0.141 inches

First Diameter From Head:

Between 0.081 inches and 0.086 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.302 inches and 0.322 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq+35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 4s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0