## NSN 5305-01-356-3666

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-356-3666 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.620 inches and 0.640 inches **Fastener Length:** Between 2.100 inches and 2.140 inches **Head Style:** Knurled no. 5 **Head Diameter:** Between 1.230 inches and 1.270 inches **Head Height:** 1.120 inches **Shoulder Diameter:** 0.735 inches all shoulders and 0.745 inches all shoulders **Shoulder Length:** 0.360 inches all shoulders and 0.380 inches all shoulders **Point Style:** Flat **End Application:** Pacer dawn **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 **Shoulder Shape:** Round all shoulders **Special Features:** Next assembly 3661064 Material: Steel comp 630 or steel comp xm-12 **Material Specification:** Ams5643 assn standard 1st material response and ams5659 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unf

Shelf Life:

N/a

## NSN 5305-01-356-3666

Thumbscrew - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0