## NSN 5305-01-356-7209

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-356-7209

	I Class:
3a	
	I Direction:
Right-h	
Thread	I Length:
0.345 i	nches
Fasten	er Length:
Betwee	en 0.642 inches and 0.672 inches
Head S	Style:
Flat co	untersunk
Head D	Diameter:
Betwee	en 0.328 inches and 0.338 inches
Grip D	iameter:
Betwee	en 0.1885 inches and 0.1895 inches
Interna	al Drive Style:
Offset	cruciform (torque set)
Thread	I Diameter:
0.190 i	nches
Grip Lo	ength:
Betwee	en 0.302 inches and 0.322 inches
Thread	ly Qty Per Inch (tpi):
32	
Min. Te	ensile Strength (psi):
160000	) pounds per square inch
Counte	ersink Angle:
Betwee	en 99.0 degrees and 101.0 degrees
Materia	al:
Iron all	by 660 fastener
Materia	al Specification:
Ams57	37 assn standard 1st material response fastener or ams5731 assn standard 2nd material response fastene
Surfac	e Treatment:
Passiva	ate fastener
Surfac	e Treatment Specification:
Qq-p-3	5 federal specification single treatment response fastener
Thread	I Series Designator:
Unjf	
Shelf L	.ife:
N/a	

## NSN 5305-01-356-7209

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

