## NSN 5305-01-356-7210



Panel Screw Assembly - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-356-7210 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** 0.390 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.420 inches **Head Height:** 0.495 inches **Internal Drive Style:** Slot **Material Accommodated Thickness:** Between 0.156 inches and 0.217 inches **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Product Name:** Navy special project Material: Aluminum alloy 6061 headsteel secondary washersteel comp 301 primary washerstainless steel springaluminum alloy 6061 stand-offstainless steel fastener **Material Specification:** Qq-a-225/8 federal specification single material response headmil-s-5059 military specification single material response primary washerastm a580 assn standard single material response springqq-a-225/8 federal specification single material response stand-offastm a493 assn standard single material response fastener **Surface Treatment:** Anodize headcadmium secondary washer and chromate secondary washerpassivate primary washeranodize stand-offpassivate fastener **Surface Treatment Specification:** Mil-a-8625, ty1, cl1 military specification single treatment response headqq-p-416, ty2, cl2 federal specification single treatment response

Mil-a-8625, ty1, cl1 military specification single treatment response headqq-p-416, ty2, cl2 federal specification single treatment response secondary washerqq-p-35 federal specification single treatment response primary washermil-a-8625, ty1, cl1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener

	•		
Thread	Sarias	I Jacian	otor.
IIII Gau	OCI ICO	Desidi	iatoi .

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

. . . . .