## NSN 5305-01-356-8978

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-356-8978 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** Between 3.953 inches and 4.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.3108 inches and 0.3117 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches **Grip Length:** Between 3.428 inches and 3.448 inches Width Across Flats: Between 0.1885 inches and 0.1905 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas335 professional/industrial association standard Shelf Life: N/a

. **.**, a

**Unit Of Measure:** 

--

## NSN 5305-01-356-8978

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0