2a

6

13

Socket Head Cap Screw - Page 1 of 2





**Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.441 inches and 0.625 inches Fastener Length: Between 0.595 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches Hole Diameter: Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches Hole Quantity: Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b **Minimum Yield Strength:** 30000 pounds per square inch Hole Configuration Style: Round internal hexagon **Product Name:** Navy special project Material: Stainless steel **Material Specification:** Astma493 assn standard single material response

## NSN 5305-01-357-0984

Socket Head Cap Screw - Page 2 of 2



Surface Treatment: Passivate Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unrc

**Specification Data:** 

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0