NSN 5305-01-358-1013

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-358-1013 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.412 inches **Fastener Length:** 0.412 inches **Head Style:** Hexagon **Head Height:** Between 0.173 inches and 0.203 inches Width Between Flats: Between 0.173 inches and 0.203 inches Washer Quantity: **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Secondary Washer Relationship To Primary Washer:** Identical **Hole Thread Diameter:** 0.219 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** 0.032 inches **Product Name:** Navy special project **Special Features:** Threaded internal drive Material: Steel **Surface Treatment:** Cadmium and chromate or chromate and zinc **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification 1st treatment response or qq-z-325 ty2 cl3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-358-1013

Assembled Washer Screw - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0