## NSN 5305-01-358-6674

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-358-6674

Thread Class:
A3a
Thread Direction:
Right-hand
Thread Length:
0.363 inches
Fastener Length:
Between 1.536 inches and 1.566 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.258 inches and 0.305 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.190 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 100.0 degrees
Surface Finish:
63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1581 professional/industrial association standard
Shelf Life:

N/a

## NSN 5305-01-358-6674

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0