

View Online at <https://aerobasegroup.com/nsn/5305-01-358-6675>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.145 inches and 0.165 inches

**Fastener Length:**

Between 0.610 inches and 0.640 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.134 inches and 0.138 inches

**Head Height:**

0.320 inches

**Internal Drive Style:**

Hexagon

**Material Accommodated Thickness:**

0.075 inches

**Thread Diameter:**

0.138 inches

**Width Across Flats:**

0.094 inches

**Thready Qty Per Inch (tpi):**

32

**Product Name:**

Navy special project

**Color:**

Black stand-off

**Material:**

Steel comp 301 spring or steel comp 302 spring or steel comp 302b spring or steel comp 303 spring or steel comp 303se spring or steel comp 304 spring or steel comp 304l spring or steel comp 305 spring or steel comp 308 spring or steel comp 309 spring or steel comp 309s spring or steel comp 310 spring or steel comp 310s spring or steel comp 314 spring or steel comp 316 spring or steel comp 316l spring or steel comp 317 spring or steel comp 321 spring or steel comp 347 spring or steel comp 348 spring or steel comp 384 spring or steel comp 385 spring or steel comp 303 plus x spring or steel comp 303cu spring or steel comp 303ma springaluminum alloy 7075 stand-offsteel comp 301 fastener or steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fastener or steel comp 314 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener or steel comp 303 plus x fastener or steel comp 303cu fastener or steel comp 303ma fastener

**Material Specification:**

Qqa225/9 federal specification single material response stand-off

**Surface Treatment:**

Passivate springanodize stand-offpassivate fastener

**Surface Treatment Specification:**

Qq+35 federal specification single treatment response springmils8625 ty2cl2 military specification single treatment response stand-offq+35

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

spec.