NSN 5305-01-358-7304

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-358-7304 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.360 inches **Fastener Length:** 0.800 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches Point Length: 0.109 inches First Diameter From Head: Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.440 inches **Point Style:** Cone **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 77.0 degrees and 87.0 degrees Material: Stainless steel **Material Specification:** 66, 300 series federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Unf

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5305-01-358-7304

Externally Relieved Body Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0