Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-358-7305

Thread Class:
Thread Direction:
Right-hand
Thread Length:
Between 0.125 inches and 0.140 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.191 inches and 0.225 inches
Head Height:
Between 0.040 inches and 0.055 inches
First Diameter From Head:
Between 0.081 inches and 0.086 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.205 inches and 0.250 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
60000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Externally Relieved Body Diameter Quantity:
1
Material:
Stainless steel
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, ty2 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0