## NSN 5305-01-358-7388

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-358-7388 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.776 inches and 0.929 inches **Fastener Length:** 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.452 inches and 0.507 inches **Locking Feature:** Patch or strip **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 60000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Stainless steel **Locking Feature Material:** Plastic polyamide **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Passivate or oxide **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response or mil-c-13924, cl3 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-358-7388

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.