

View Online at <https://aerobasegroup.com/nsn/5305-01-358-8092>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.658 inches and 0.750 inches

**Fastener Length:**

Between 0.720 inches and 0.750 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.105 inches and 0.120 inches

**Width Between Flats:**

Between 0.305 inches and 0.312 inches

**Internal Drive Style:**

Slot

**End Application:**

Mrap-caiman

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 302b or steel comp 303cu or steel comp 309 or steel comp 310 or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0