NSN 5305-01-358-8093

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-358-8093

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.338 inches |
| Fastener Length: |
| Between 1.700 inches and 1.730 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.294 inches and 0.332 inches |
| Internal Drive Style: |
| Torque-set ribbed |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Screw Material: |
| Titanium alloy uns r56400 |
| Screw Material Specification: |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Bearing Surface Of Head Surface Finish: |
| 32.0 microinches |
| Shank Surface Finish: |
| 32.0 microinches |
| Thread Surface Finish: |
| 32.0 microinches |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1221 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5305-01-358-8093

Machine Screw - Page 2 of 2

Fiig: A500d0

