NSN 5305-01-358-8403

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-358-8403

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.050 inches and 1.150 inches
Fastener Length:
Between 1.150 inches and 1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.312 inches and 0.316 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
80000 pounds per square inch
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 304 or steel comp 384 or steel comp 316 or steel comp 305
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Specification Or Standard:
Specification Or Standard: 1 type and 49 style Shelf Life:
1 type and 49 style

NSN 5305-01-358-8403

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0