## NSN 5305-01-359-0341

Machine Screw - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5305-01-359-0341



## 3a **Thread Direction: Right-hand Thread Length:** Between 0.469 inches and 0.500 inches Fastener Length: Between 0.469 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.296 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches Locking Feature: Patch or pellet or strip **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 Locking Feature Material: Plastic polyamide **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, ty2, cl2 federal specification all treatment responses **Special Features:** Offset cruciform recess per ms33781 **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1191 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-359-0341

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

