NSN 5305-01-359-1473

Machine Screw - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5305-01-359-1473



3a **Thread Direction: Right-hand Thread Length:** Between 0.282 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.265 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches Hole Diameter: Between 0.034 inches and 0.042 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.164 inches **Hole Quantity:** 2 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5737 assn standard single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response Head Hole Configuration Style: Round longitudinal hole Bearing Surface Of Head Surface Finish: 32.0 microinches Shank Surface Finish: 32.0 microinches **Thread Surface Finish:** 32.0 microinches

NSN 5305-01-359-1473

Machine Screw - Page 2 of 2



Thread Series Designator:

Unjc

Specification Data:

80205-nas1101 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0