Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-359-2289

view Online at https://aerobasegroup.com/nsr/3503-01-359-2269
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
2.250 inches
Fastener Length:
Between 2.900 inches and 3.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 1.293 inches and 1.312 inches
Head Height:
Between 0.864 inches and 0.875 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.875 inches
Width Across Flats:
Between 0.750 inches and 0.757 inches
Thready Qty Per Inch (tpi):
14
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or mms5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-416, ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-01-359-2289

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

