

View Online at <https://aerobasegroup.com/nsn/5305-01-359-2290>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

2.250 inches

**Fastener Length:**

5.000 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 1.293 inches and 1.312 inches

**Head Height:**

Between 0.864 inches and 0.865 inches

**Locking Feature:**

Strip locking feature

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.875 inches

**Width Across Flats:**

Between 0.750 inches and 0.757 inches

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Color:**

Black fastener

**Material:**

Plastic polyamide locking featureiron alloy 660 fastener

**Material Specification:**

Ams5731 assn standard single material response fastener or ams5737 assn standard single material response fastener

**Surface Treatment:**

Oxide fastener

**Surface Treatment Specification:**

Mil-c-13924, cl1 military specification single treatment response fastener

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.