NSN 5305-01-359-2291

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-359-2291 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.342 inches **Fastener Length:** 0.425 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.3390 inches and 0.3813 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.125 inches and 0.128 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Coat with chlorine-free cetyl alcohol lubricant Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83488, ty2, cl3 military specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-359-2291

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.