

View Online at <https://aerobasegroup.com/nsn/5305-01-359-2298>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.367 inches and 0.388 inches

**Fastener Length:**

Between 1.289 inches and 1.309 inches

**Head Style:**

Crowned hexagon

**Head Height:**

Between 0.126 inches and 0.146 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3737 inches and 0.3742 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.750 inches and 0.766 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

90000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.181 inches first hole and 1.161 inches first hole

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip

**Special Features:**

Two locking balls or elements on grip

**Material:**

Nickel alloy 600 spring or nickel alloy x-750 springiron alloy 660 fastener

**Material Specification:**

Qq-w-390 federal specification 1st material response spring or ams5699 assn standard 2nd material response springams5737 assn standard single material response fastener

**Surface Treatment:**

Passivate springpassivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response springqq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0