

View Online at <https://aerobasegroup.com/nsn/5305-01-359-4632>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.679 inches and 0.750 inches

Fastener Length:

0.750 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.365 inches and 0.375 inches

Head Height:

Between 0.244 inches and 0.250 inches

Locking Feature:

Strip threads or pellet threads or patch threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

Between 0.187 inches and 0.190 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Plastic polyamide locking featureiron alloy 660 fastener

Material Specification:

Ams5731 assn standard single material response fastener and ams5737 assn standard single material response fastener

Precious Material And Location:

silver

Precious Material:

Silver

Surface Treatment:

Silver fastener

Surface Treatment Specification:

Ams2411 assn standard single treatment response fastener

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0