NSN 5305-01-359-4633

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-359-4633 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.857 inches and 1.000 inches **Fastener Length:** 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Locking Feature:** Strip threads or patch threads or pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.312 inches and 0.316 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Precious Material And Location:** silver **Precious Material:** Silver **Surface Treatment:** Silver silver fastener **Surface Treatment Specification:** Ams2411 assn standard single treatment response ams2411 assn standard single treatment response fastener **Thread Series Designator:** Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

NSN 5305-01-359-4633

Socket Head Cap Screw - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0