

View Online at <https://aerobasegroup.com/nsn/5305-01-359-4633>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.857 inches and 1.000 inches

**Fastener Length:**

1.000 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.550 inches and 0.562 inches

**Head Height:**

Between 0.368 inches and 0.375 inches

**Locking Feature:**

Strip threads or patch threads or pellet threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.312 inches and 0.316 inches

**Thread Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Plastic polyamide locking featureiron alloy 660 fastener

**Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

**Precious Material And Location:**

silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver silver fastener

**Surface Treatment Specification:**

Ams2411 assn standard single treatment response ams2411 assn standard single treatment response fastener

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0