NSN 5305-01-359-4635

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-359-4635 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.576 inches **Fastener Length:** 2.365 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.853 inches and 0.875 inches **Head Height:** Between 0.368 inches and 0.375 inches **Shoulder Diameter:** 0.622 inches first shoulder and 0.623 inches first shoulder **Shoulder Length:** 1.620 inches first shoulder and 1.630 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder **Special Features:** Threads undercut for relief 0.154 in. Wide max., 0.406 in. Nom. Dia. Material: Steel **Surface Treatment:** Zinc **Thread Series Designator:**

Unrc Shelf Life: N/a

NSN 5305-01-359-4635

Shoulder Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0