

View Online at <https://aerobasegroup.com/nsn/5305-01-359-4637>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.528 inches

Fastener Length:

Between 2.026 inches and 2.056 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.010 inches and 1.080 inches

Grip Diameter:

Between 0.7486 inches and 0.7490 inches

Internal Drive Style:

Tri-wing recess

Thread Diameter:

0.750 inches

Grip Length:

Between 1.366 inches and 1.386 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches grip 32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4812 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0