

View Online at <https://aerobasegroup.com/nsn/5305-01-359-4729>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

Between 0.599 inches and 0.629 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.461 inches

**Internal Drive Style:**

Torque-set ribbed

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Screw Material Specification:**

Mil-s-5000 military specification single material response or mil-s- military specification 1st material response or mil-s-6049 military specification 2nd material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Bearing Surface Of Head Surface Finish:**

32.0 microinches

**Shank Surface Finish:**

32.0 microinches

**Thread Surface Finish:**

32.0 microinches

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5000 spec.