Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-359-8747

| Thread Direction: |
|--|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 28.20 millimeters and 35.30 millimeters |
| Fastener Length: |
| Between 34.70 millimeters and 35.30 millimeters |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 7.24 millimeters and 7.76 millimeters |
| Width Between Flats: |
| Between 17.73 millimeters and 18.00 millimeters |
| Thread Diameter: |
| 12.0 millimeters |
| Min. Tensile Strength (psi): |
| 1040 megapascals |
| Hardness Rating: |
| 33.0 rockwell c and 39.0 rockwell c |
| Minimum Yield Strength: |
| 940 megapascals |
| Thread Pitch In Millimeters: |
| 1.75 |
| External Thread Tolerance Class: |
| 6g |
| Material: |
| Steel property class 10.9 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2 cl 3 federal specification single treatment response |
| Thread Series Designator: |
| Μ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |
| |