

View Online at <https://aerobasegroup.com/nsn/5305-01-359-9436>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.304 inches and 0.375 inches

**Fastener Length:**

0.375 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.176 inches and 0.181 inches

**Head Height:**

Between 0.108 inches and 0.112 inches

**Locking Feature:**

Patch threads or pellet threads or strip threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

Between 0.094 inches and 0.095 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Plastic polyamide locking feature iron alloy 660 fastener

**Material Specification:**

Ms5731 assn standard single material response fastener or ams5737 assn standard single material response fastener

**Precious Material And Location:**

silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver fastener

**Surface Treatment Specification:**

Ams2411 assn standard single treatment response fastener

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0