NSN 5305-01-359-9436

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-359-9436 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.304 inches and 0.375 inches **Fastener Length:** 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.181 inches **Head Height:** Between 0.108 inches and 0.112 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener **Material Specification:** Ms5731 assn standard single material response fastener or ams5737 assn standard single material response fastener **Precious Material And Location:** silver **Precious Material:** Silver **Surface Treatment:** Silver fastener **Surface Treatment Specification:** Ams2411 assn standard single treatment response fastener

Thread Series Designator: Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

NSN 5305-01-359-9436

Socket Head Cap Screw - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0