## NSN 5305-01-359-9446

Shoulder Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-359-9446

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.438 inches  |
| Fastener Length:  |
| Between 1.402 inches and 1.406 inches                       |
| Head Style:   |
| Flat chamfer  |
| Head Diameter:  |
| Between 0.419 inches and 0.437 inches                       |
| Head Height:  |
| Between 0.213 inches and 0.219 inches                       |
| Shoulder Diameter:  |
| 0.308 inches first shoulder and 0.310 inches first shoulder |
| Shoulder Length:  |
| 0.745 inches first shoulder and 0.755 inches first shoulder |
| Internal Drive Style:                                       |
| Hexagon   |
| Thread Diameter:  |
| 0.250 inches  |
| Width Across Flats:   |
| 0.156 inches  |
| Thready Qty Per Inch (tpi):                                 |
| 20  |
| Shoulder Shape:   |
| Round first shoulder  |
| Material:   |
| Nickel alloy 400 or nickel alloy r-405                      |
| Material Specification:                                     |
| Qq-n-281 federal specification all material responses       |
| Thread Series Designator:                                   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| <br>Demilitarization:                                       |
| No  |
|   |
| Fiig:   |
| A003b0  |