NSN 5305-01-360-3302



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-360-3302 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.750 inches **Fastener Length:** Between 2.546 inches and 2.593 inches **Head Style:** Hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Bearing Surface Of Head Surface Finish:** 63.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjf **Specification Data:**

Unit Of Measure:

N/a

Shelf Life:

80205-nas1801 professional/industrial association standard

NSN 5305-01-360-3302

Machine Screw - Page 2 of 2



Demi			

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.