

View Online at <https://aerobasegroup.com/nsn/5305-01-360-6058>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.250 inches and 0.280 inches

**Fastener Length:**

Between 0.660 inches and 0.690 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**First Diameter From Head:**

Between 0.080 inches and 0.084 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.410 inches

**Internal Drive Style:**

W/o internal drive

**Thread Diameter:**

0.112 inches

**Thread Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Color:**

Gold

**Material:**

Steel comp 304 or steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification single material response or ml-s-5000 military specification single material response or mil-s-s6049 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.