NSN 5305-01-360-6058

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-360-6058 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.280 inches **Fastener Length:** Between 0.660 inches and 0.690 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.080 inches and 0.084 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.410 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Color: Gold Material: Steel comp 304 or steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification single material response or ml-s-5000 military specification single material response or mil-s-s6049 military specification single material response **Surface Treatment:** Cadmium and chromate

Thread Series Designator:

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Unjc

NSN 5305-01-360-6058

Externally Relieved Body Screw - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-s-5626 spec.

Shelf Life: