NSN 5305-01-360-6059

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-360-6059 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.178 inches and 0.198 inches **Fastener Length:** Between 0.547 inches and 0.577 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.167 inches and 0.177 inches **Head Height:** Between 0.092 inches and 0.122 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.365 inches and 0.385 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 or steel comp 303ma or steel comp 303se or steel comp 416 or steel comp 303 plus x **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072-e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0

NSN 5305-01-360-6059

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072-e300 spec.