## NSN 5305-01-360-6067

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-360-6067 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.467 inches **Fastener Length:** Between 1.013 inches and 1.060 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.310 inches and 0.312 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 52.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837 cl3 ty2 military specification single treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5305-01-360-6067

Close Tolerance Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.