NSN 5305-01-360-6068

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-360-6068 **Thread Class:** За **Thread Direction:** Right-hand **Thread Length:** Between 0.295 inches and 0.325 inches **Fastener Length:** Between 0.480 inches and 0.520 inches **Head Height:** 0.170 inches **Internal Drive Style:** Cross recess type 1 **Material Accommodated Thickness:** Between 0.480 inches and 0.520 inches **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Material: Aluminum alloy 7075 bearing surface of headsteel comp 302 threads or steel comp 303 threads or steel comp 303se threads or steel comp 304 threads or steel comp 304l threads or steel comp 305 threads or steel comp 309 threads or steel comp 310 threads or steel comp 316 threads or steel comp 316l threads or steel comp 317 threads or steel comp 321 threads or steel comp 321 threads or steel comp 320 threads or steel threads or steel comp 324 threads or steel comp 347 threads **Material Specification:** Qq-a-225/9 federal specification single material response bearing surface of head **Surface Treatment:** Chromate bearing surface of headpassivate threads **Surface Treatment Specification:** Mil-c-5541 cl3 military specification single treatment response bearing surface of headqq-p-35 federal specification single treatment response threads **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Mil-std (military Standard): Mil-c-5541 spec.

No Fiig: A003b0