## NSN 5305-01-360-9142

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-360-9142 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.222 inches and 0.242 inches **Fastener Length:** Between 0.540 inches and 0.560 inches **Head Style:** Undercut pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches **First Diameter From Head:** Between 0.094 inches and 0.096 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c and 47.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 630 **Material Specification:** Mil-c-24111 military specification single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-01-360-9142

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-24111 spec.