NSN 5305-01-360-9163

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-360-9163

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.363 inches
Fastener Length:
Between 1.973 inches and 2.003 inches
Head Style:
Flat countersunk
Head Diameter:
0.339 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.190 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military
specification 3rd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5305-01-360-9163

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.