Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-361-1409

Т	hread Class:
3	a
Т	hread Direction:
R	ight-hand
Т	hread Length:
В	etween 0.120 inches and 0.130 inches
F	astener Length:
В	etween 0.984 inches and 1.016 inches
н	ead Style:
K	nurled no. 2
Н	ead Diameter:
В	etween 0.500 inches and 0.505 inches
Н	ead Height:
0.	250 inches
F	irst Diameter From Head:
В	etween 0.125 inches and 0.135 inches
D	istance From Largest Bearing Surface Of Head To End Of First Diameter:
В	etween 0.870 inches and 0.890 inches
In	iternal Drive Style:
S	lot
Т	hread Diameter:
0.	190 inches
Т	hready Qty Per Inch (tpi):
32	2
Ε	xternally Relieved Body Diameter Quantity:
1	
	laterial:
	teel comp 303
	laterial Specification:
	stm d582 assn standard single material response
	urface Treatment:
	assivate
	urface Treatment Specification:
	q-p-35 federal specification single treatment response
	hread Series Designator:
	nf
	helf Life:
U	nit Of Measure:
	emilitarization:
N	0

NSN 5305-01-361-1409

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

